

ANDERSON CHEMICAL COMPANY
325 South Davis Avenue
Litchfield, MN 55355
800-366-2477
www.ACCommN.COM



CENTRAL FOAM SANITIZE STATION

The “CENTRAL FOAM SANITIZE STATION” will accomodate up to 4 products and can be customized to accomodate more, if necessary.

- 3/4 Air-Operated Double Diaphragm feed pumps. Single or dual product proportioners. 4.5, 9 or 18 gpm fill rate.
- 11 gallon polyethylene tanks.
- Eliminates concentrated product on production floor. Pre-diluted product pumped from chemical area to application points.



Wall mount version also available.

SANITATION TECHNOLOGIES

CENTRAL FOAM SANITIZE STATION

Page 2

Just The Right Chemistry.[®]

FEATURES & BENEFITS

- Smart relays allow for operation at specific times of the day and specific timing intervals.
- Independent relays allow for accurate and repeatable on/off functions.
- Regulated air pressure results from the added regulator attached.
- Colored push button are specific for products used in conjunction with industrial standards.
 - **Blue** for alkaline products
 - **Red** for acidic products
 - **Yellow** for chlorine and stronger oxidizing products
 - **Green** for neutral pH products
- Air-Operated Double Diaphragm pumps used for dependable product delivery.
 - Polypro available when using non-oxidizing products
 - Kynar used for specific product applications
- White Board Mounting provides a clean and sanitary appearance while providing a maintenance free environment.
- Pick up systems include ID Tags, foot valves and check valves for the prevention of siphoning, back flow and misreading of drums.
- Complete installation includes all chemical lines from drum to point of use.
- Dispensing pumps are ID Tagged for ease of reading and safety.

CONTROL FUNCTION

- Smart relays
- Dayton timers
- Emergency stop

SPECIFICATIONS

- 110 volt electrical power required to activate the unit
- 50 psi minimum air supply (filtered of water and oil contaminants)
- 7 scfm air volume required

OPTIONS

- Additional manual push buttons available for added product applications
- Built-in timer allows run time to be set and adjusted easily

SINCE 1911